DEFENDER 110 STANDARD

SPECIFICATIONS

Feature and equipment changes from 110 S variant

110 D250 STANDARD

Sound system in lieu of Meridian Sound System

No roof rails 18" steel wheels in lieu of 19" alloys 18" steel spare wheel in lieu of 19" spare No spare wheel lock No heated seats

From **£62,795**

Vehicle prices shown including VAT, delivery charges, and estimated government fees and duties.

Light Cloud headlining in lieu of Ebony Morzine headlining

224

CO₂ Emissions (from) (g/km)

33.1 Fuel consumption (up to) (mpg)

The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real world figures may differ. CO₂, Equivalent All-Electric Range (EAER) and fuel economy figures shown on this website are estimated and may vary according to wheel fitment and optional extras fitted. Definitive CO₂, Equivalent All-Electric Range (EAER) and fuel economy figures will be confirmed by your retailer prior to order confirmation, together with final On the Road pricing. WLTP is the new official EU test used to calculate standardised fuel consumption and CO₂ figures for passenger cars.

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90% fuel. † Includes full fluids and 90% fuel. ††Roof carrying is only available with fixed and sliding panoramic roofs

Maximum speed mph (km/h)	117 (188)
Acceleration secs 0-60mph (0-100 km/h)	7.9 (8.3)
POWERTRAIN	
Capacity (cc)	2,997
Maximum power (HP/rpm)	249 / 4,000
Maximum torque (Nm/rpm)	570 / 1,250 - 2,500
Transmission	Automatic
Tank capacity (litres approx.)	89
WEIGHTS (KG)*	
Unladen weight (EU)**	2,436 (5 seats) 2,506 (5+2 seats)
Unladen weight (DIN) †	2,361 (5 seats) 2,431 (5+2 seats)
Gross Vehicle Weight (GVW) (kg)	3,200 (5 seats) 3,280 (5+2 seats)
TOWING	
Unbraked trailer (kg)	750
Maximum towing (kg)	3,500 (5 seats) 3,495 (5+2 seats)
Maximum coupling point (nose weight) (kg)	150
Maximum vehicle and trailer combination (GTW) (kg)	6,700 (5 seats) 6,775 (5+2 seats)
ROOF CARRYING (KG) ^{††}	
Maximum roof load (including cross bars) (kg)	100 (All-Season Tyres) 168 (All-Terrain Tyres)
DIMENSIONS	
Height (mm)	1,972 (Coil Suspension) 1,967 (Air Suspension)
Length (mm)	4,758 (Without spare wheel) 5,018 (With spare whee
Width with mirrors folded (mm)	2,008
Width with mirrors out (mm)	2,105
Front wheel track (mm)	1,704 (Coil Suspension) 1,706 (Air Suspension)
Rear wheel track (mm)	1,700 (Coil Suspension) 1,702 (Air Suspension)
Wheelbase (mm)	3,022
HEADROOM	
Maximum first row / second row / third row headroom with standard roof (mm)	1,032 / 1,025 / NA (5 seats) 1,032 / 1,025 / 1,041 (5+2 seats)
Maximum first row / second row / third row headroom with panoramic/fabric roof (mm)	1,032 / 1,025 / NA (5 seats) 1,032 / 1,025 / 1,041 (5+2 seats)
LEGROOM	
Maximo una firat raur / accord raur / third raur	002 / 002 / NIA /E apata) 002 / 075 / 517 /5 2 apata)

993 / 992 / NA (5 seats) | 993 / 975 / 517 (5+2 seats)

Maximum first row / second row / third row

legroom (mm)

Height (mm)	904
Width (mm)	1,211 (5 seats) 1,188 (5+2 seats)
Width between arches (mm)	1,160
Length behind first row (mm)	1,763 (5 seats) 1,789 (5+2 seats)
Maximum loadspace volume behind first row - Dry (litres)	1,875 (5 seats) 1,826 (5+2 seats)
Maximum loadspace volume behind first row - Wet (litres)	2,277 (5 seats) 2,233 (5+2 seats)
Length behind second row (mm)	919 (5 seats) 900 (5+2 seats)
Maximum loadspace volume behind second row - Dry (litres)	786 (5 seats) 743 (5+2 seats)
Maximum loadspace volume behind second row - Wet (litres)	972 (5 seats) 916 (5+2 seats)
Length behind third row (mm)	289
Maximum loadspace volume behind third row - Dry (litres)	160
Maximum loadspace volume behind third row - Wet (litres)	231
GROUND CLEARANCE - STANDARD	
Ride height (mm)	228 (Coil Suspension) 218 (Air Suspension)
Approach angle	31.2° (Coil Suspension) 30.1° (Air Suspension)
Departure angle	37.8° (Coil Suspension) 37.7° (Air Suspension)
Pamp anglo	22 6° (Coil Suspension) 22 0° (Air Suspension)

Ride height (mm)	228 (Coil Suspension) 218 (Air Suspension)
Approach angle	31.2° (Coil Suspension) 30.1° (Air Suspension)
Departure angle	37.8° (Coil Suspension) 37.7° (Air Suspension)
Ramp angle	22.6° (Coil Suspension) 22.0° (Air Suspension)

GROUND CLEARANCE - OFF ROAD

Ride height (mm)	_
Approach angle	-
Departure angle	
Ramp angle	

WADING DEPTH

Maximum wading depth (mm)	850 (Coil Suspension) 900 (Air Suspension)
5 1 , ,	· · · · · · · · · · · · · · · · · · ·

TURNING CIRCLE

Kerb-to-kerb (m)	12.84
Wall-to-wall (m)	13.1
Turns lock-to-lock (no. of turns)	2.7

CONTACT YOUR RETAILER