

SPECIFICATIONS

Unpainted brake calipers
Non-heated steering wheel
20-way front seats in lieu of 24-way
Three-zone climate control
Meridian 3D Surround Sound system in lieu of Meridian Signature Sound System

Vehicle prices shown including VAT, delivery charges, and estimated government fees and duties.

200 37 1

CO₂ Emissions (from) (g/km)

Fuel consumption (up to) (mpg)

Non-heated steering wheel
20-way front seats in lieu of 24-way
Pixel LED headlights
Meridian Sound system in lieu of Meridian 3D Surround Sound System
Powered upper and lower tailgate in lieu of powered gesture tailgate

Vehicle prices shown including VAT, delivery charges, and estimated government fees and duties.

201 36.8

CO₂ Emissions (from) (g/km)

Fuel consumption (up to) (mpg)

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90% fuel. † Includes full fluids and 90% fuel. ††Roof carrying is only available with fixed and sliding panoramic roofs.

Maximum speed mph (km/h)	145 (234)
Acceleration (secs) 0-60 mph (0-100 km/h) with Dynamic Launch	5.7 (6.0)

Capacity (cc)	2,997
Maximum power (HP/rpm)	350 / 4,000
Maximum torque (Nm/rpm)	700 / 1,500 - 3,000
Transmission	Automatic
Fuel tank capacity – useable litres	80

Unladen weight (EU)**	2,569 / 2,666
Unladen weight (DIN)†	2,494 / 2,541
Gross Vehicle Weight (GVW)	3,390 / 3,400

Unbraked trailer	750
Maximum towing	3,500
Maximum coupling point (nose weight)	150
Maximum vehicle and trailer combination	6,890 / 6,900

Maximum roof load (including cross bars)	100
--	-----

Maximum height (mm)	1,867
Overall length (mm)	5,252
Width with mirrors folded (mm)	2,047
Width with mirrors out (mm)	2,209
Front wheel track (mm)	1,700.3
Rear wheel track (mm)	1,702.3
Wheelbase (mm)	3,197

Maximum front row headroom (mm)	999
Maximum second row headroom (mm)	978.3 / 1,005
Maximum third row headroom (mm)	909

Maximum front row legroom	1,014
Maximum second row legroom	1,220 / 1,027
Maximum third row legroom	864

Height	845.8
Width (mm)	1,444 / 1,255
Width between arches (mm)	1,057.3 / 1,059
Length behind first row (mm)	1,975.5 / 2,165
Maximum loadspace volume behind first row - Dry (litres)	2,176 / 2,050
Maximum loadspace volume behind first row - Wet (litres)	2,727.6 / 2,601
Length behind second row (mm)	1,093 / 1,286
Maximum loadspace volume behind second row - Dry (litres)	818 / 857
Maximum loadspace volume behind second row - Wet (litres)	1,050 / 1,061
Length behind third row (mm)	434
Maximum loadspace volume behind third row - Dry (litres)	212
Maximum loadspace volume behind third row - Wet (litres)	312

Approach angle	26.1°
Departure angle	24.5°
Ramp angle	21.5° / 20.1°

Approach angle	34.7°
Departure angle	29.0°
Ramp angle	20.1°

Maximum wading depth (mm)	900
---------------------------	-----

Kerb-to-kerb steering (m)	11.54
Wall-to-wall steering (m)	11.96
Turns lock-to-lock (no. of turns)	2.78

CONTACT YOUR RETAILER