## RANGE ROVER P530 LWB / LWB 7-SEATS

# SPECIFICATIONS

Feature and equipment changes from Autobiography variant

#### **P530 LONG WHEELBASE**

No configurable programs

Pixel LED Headlights with signature DRL in lieu of Digital LED headlights

Unpainted brake calipers

No heated steering wheel

Meridian 3D Surround Sound System

No privacy glass

20-way heated & ventilated seat in lieu of 24-way heated and cooled, massage electric front seats with Executive Class rear seats

Three-zone Climate Control

From **£ 147,745** 

Vehicle prices shown including VAT, delivery charges, and estimated government fees and duties.

18

CO<sub>2</sub> Emissions (from) (g/km)

369.5
Fuel consumption (up to) (mpg)

#### P530 LONG WHEELBASE 7-SEATS

Non-heated steering wheel

Pixel LED headlights in lieu of Digital LED Headlights

Meridian 3D Surround Sound System in lieu of Meridian Signature Sound System

Auto-dimming interior rear view mirror in lieu of ClearSight interior rear view mirror

Unpainted brake calipers

From **£ 147,745** 

Vehicle prices shown including VAT, delivery charges, and estimated government fees and duties.

24

CO<sub>2</sub> Emissions (from) (g/km)

**266**Fuel consumption (up to) (mpg)

#### PERFORMANCE

PERFORMANCE		
Maximum speed mph (km/h)	155 (250)	
Acceleration (secs) 0-60 mph (0-100 km/h) with  Dynamic Launch	4.5 (4.7) / 4.6 (4.8)	
POWERTRAIN		
Capacity (cc)	2,997	
Maximum power (HP/rpm)	530 / 5,000 - 7,000	
Maximum torque (Nm/rpm)	750 / 1,800 - 4,500	
Transmission	Automatic	
Fuel tank capacity – useable litres	90	
WEIGHTS (KG)*		
Unladen weight (EU)**	2,708 / 2,810	
Unladen weight (DIN)†	2,663 / 2,735	
Gross Vehicle Weight (GVW)	3,400 / 3,480	
TOWING (KG)		
Unbraked trailer	750	
Maximum towing	3,500	
Maximum coupling point (nose weight)	150	
Maximum vehicle and trailer combination	6,900 / 6,980	
ROOF CARRYING (KG)††		
Maximum roof load (including cross bars)	100	
DIMENSIONS		
Maximum height (mm)	1,867	
Overall length (mm)	5,252	
Width with mirrors folded (mm)	2,047	
Width with mirrors out (mm)	2,209	
Front wheel track (mm)	1,700.3	
Rear wheel track (mm)	1,702.3	
Wheelbase (mm)	3,197	
HEADROOM		
Maximum front row headroom (mm)	999	
Maximum second row headroom (mm)	978.3 / 1,005	

### LEGROOM (MM)

Maximum first row legroom	1,014	
Maximum second row legroom	1,220 / 1,027	
LOADSPACE CAPACITY		
Height	845.8	
Width (mm)	1,444 / 1,255	
Width between arches (mm)	1,057.3 / 1,059	
Length behind first row (mm)	2,165 / 2,175	
Maximum loadspace volume behind first row - Dry (litres)	2,176 / 2,050	
Maximum loadspace volume behind first row - Wet (litres)	2,727.6 / 2,601	
Length behind second row (mm)	1,093 / 1,286	
Maximum loadspace volume behind second row - Dry (litres)	818 / 857	
Maximum loadspace volume behind second row	1,050 / 1,061	
- Wet (litres)		
- Wet (litres)	26.1°	
GROUND CLEARANCE - STANDARD	26.1° 24.5°	
GROUND CLEARANCE - STANDARD  Approach angle		
GROUND CLEARANCE - STANDARD  Approach angle Departure angle	24.5°	
GROUND CLEARANCE - STANDARD  Approach angle Departure angle Ramp angle	24.5°	
GROUND CLEARANCE - STANDARD  Approach angle Departure angle Ramp angle  GROUND CLEARANCE - OFF ROAD	24.5° 20.1°	
GROUND CLEARANCE - STANDARD  Approach angle Departure angle Ramp angle  GROUND CLEARANCE - OFF ROAD  Approach angle	24.5° 20.1° 34.7°	
GROUND CLEARANCE - STANDARD  Approach angle Departure angle Ramp angle  GROUND CLEARANCE - OFF ROAD  Approach angle Departure angle	24.5° 20.1° 34.7° 29.0°	
GROUND CLEARANCE - STANDARD  Approach angle Departure angle  Ramp angle  GROUND CLEARANCE - OFF ROAD  Approach angle Departure angle  Ramp angle  Ramp angle	24.5° 20.1° 34.7° 29.0°	
GROUND CLEARANCE - STANDARD  Approach angle Departure angle Ramp angle  GROUND CLEARANCE - OFF ROAD  Approach angle Departure angle Ramp angle  WADING DEPTH	24.5° 20.1°  34.7° 29.0° 25.7°	
GROUND CLEARANCE - STANDARD  Approach angle Departure angle Ramp angle  GROUND CLEARANCE - OFF ROAD  Approach angle Departure angle Ramp angle  WADING DEPTH  Maximum wading depth (mm)	24.5° 20.1°  34.7° 29.0° 25.7°	
GROUND CLEARANCE - STANDARD  Approach angle Departure angle Ramp angle  GROUND CLEARANCE - OFF ROAD  Approach angle Departure angle Ramp angle  WADING DEPTH  Maximum wading depth (mm)  TURNING CIRCLE	24.5° 20.1°  34.7° 29.0° 25.7°	

The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real world figures may differ. CO<sub>2</sub>, Equivalent All-Electric Range (EAER) and fuel economy figures shown on this website are estimated and may vary according to wheel fitment and optional extras fitted. Definitive CO<sub>2</sub>, Equivalent All-Electric Range (EAER) and fuel economy figures will be confirmed by your retailer prior to order confirmation, together with final On the Road pricing. WLTP is the new official EU test used to calculate standardised fuel consumption and CO<sub>2</sub> figures for passenger cars.

\*Weights reflect vehicles to standard specifications. Optional extras increase weight. \*\*Includes a 75kg driver, full fluids and 90% fuel. † Includes full fluids and 90% fuel. †TRoof carrying is only available with fixed and sliding panoramic roofs.