

RANGE ROVER P615 SWB

SPECIFICATIONS

Feature and equipment changes from Autobiography variant

P615 SHORT WHEELBASE

Fixed Panoramic Roof
22” wheels in lieu of 23” wheels
24-way comfort plus seats (non-haptic) in lieu of 24-way heated and ventilated, hot stone massage electric front seats (with Body and Soul Seat) with Executive Class Comfort Plus rear seats

From £ 194,745

Vehicle prices shown including VAT, delivery charges, and estimated government fees and duties.

18

CO₂ Emissions (from) (g/km)

363.4

Fuel consumption (up to) (mpg)

PERFORMANCE

Maximum speed mph (km/h)	162 (261)
Acceleration (secs) 0-60 mph (0-100 km/h) with Dynamic Launch	4.3 (4.5)

POWERTRAIN

Capacity (cc)	4,395
Maximum power (HP/rpm)	615 / 5,855 -7,000
Maximum torque (Nm/rpm)	750 / 1,800 - 5,400
Transmission	Automatic
Fuel tank capacity – useable litres	90

WEIGHTS (KG)*

Unladen weight (EU)**	2,791
Unladen weight (DIN)†	2,716
Gross Vehicle Weight (GVW)	3,380

TOWING (KG)

Unbraked trailer	750
Maximum towing	3,500
Maximum coupling point (nose weight)	150
Maximum vehicle and trailer combination	6,880

ROOF CARRYING (KG)††

Maximum roof load (including cross bars)	100
--	-----

DIMENSIONS

Maximum height (mm)	1,867
Overall length (mm)	5,052
Width with mirrors folded (mm)	2,047
Width with mirrors out (mm)	2,209
Front wheel track (mm)	1,702.3
Rear wheel track (mm)	1,704.3
Wheelbase (mm)	2,997

HEADROOM

Maximum front row headroom (mm)	999
Maximum second row headroom (mm)	996.5

LEGROOM (MM)

Maximum first row legroom	1,013
Maximum second row legroom	1,027

LOADSPACE CAPACITY

Height	845.8
Width (mm)	1,444
Width between arches (mm)	1,057.3
Length behind first row (mm)	1,975.5
Maximum loadspace volume behind first row - Dry (litres)	1,841
Maximum loadspace volume behind first row - Wet (litres)	2,335
Length behind second row (mm)	1,092.6
Maximum loadspace volume behind second row - Dry (litres)	818
Maximum loadspace volume behind second row - Wet (litres)	1,050

GROUND CLEARANCE - STANDARD

Approach angle	26.1°
Departure angle	24.5°
Ramp angle	21.5°

GROUND CLEARANCE - OFF ROAD

Approach angle	34.7°
Departure angle	29.0°
Ramp angle	27.5°

WADING DEPTH

Maximum wading depth (mm)	900
---------------------------	-----

TURNING CIRCLE

Kerb-to-kerb steering (m)	10.95
Wall-to-wall steering (m)	11.37
Turns lock-to-lock (no. of turns)	2.78

The figures provided are as a result of official manufacturer’s tests in accordance with EU legislation. For comparison purposes only. Real world figures may differ. CO₂, Equivalent All-Electric Range (EAER) and fuel economy figures shown on this website are estimated and may vary according to wheel fitment and optional extras fitted. Definitive CO₂, Equivalent All-Electric Range (EAER) and fuel economy figures will be confirmed by your retailer prior to order confirmation, together with final On the Road pricing. WLTP is the new official EU test used to calculate standardised fuel consumption and CO₂ figures for passenger cars.

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90% fuel. † Includes full fluids and 90% fuel. ††Roof carrying is only available with fixed and sliding panoramic roofs.

CONTACT YOUR RETAILER