

RANGE ROVER SPORT D300 STANDARD

SPECIFICATIONS

Feature and equipment changes from SE variant

D300 STANDARD
20” alloys in lieu of 21” alloys
No wireless device charging
8-way electric front seats with 2-way manual front headrest and power recline rear seat
No heated steering wheel
No heated windscreen
No heated seats
No heated washer jets
Standard interior
Grained leather seats in lieu of Perforated Windsor Leather
Standard metal roof in lieu of panoramic roof

From **£85,220**

Vehicle prices shown including VAT, delivery charges, and estimated government fees and duties.

191

CO<sub>2</sub> Emissions (from) (g/km)

38.7

Fuel consumption (up to) (mpg)

PERFORMANCE	
Maximum speed mph (km/h)	135 (218)
Acceleration (secs) 0-60 mph (0-100 km/h) with Dynamic Launch	6.1 (6.4)

POWERTRAIN	
Capacity (cc)	2,997
Maximum power (PS/rpm)	300 / 4,000
Maximum torque (Nm/rpm)	650 / 1,500 - 2,500
Transmission	Automatic
Fuel tank capacity – useable litres	80

WEIGHTS (KG)*	
Unladen weight (EU)**	2,390
Unladen weight (DIN)†	2,315
Gross Vehicle Weight (GVW)	3,220

TOWING (KG)	
Unbraked trailer	750
Maximum towing	3,500
Maximum coupling point (nose weight)	150
Maximum vehicle and trailer combination	6,720

ROOF CARRYING (KG)††	
Maximum roof load (including cross bars)	100

DIMENSIONS	
Maximum height (mm)	1,820
Overall length (mm)	4,946
Width with mirrors folded (mm)	2,047
Width with mirrors out (mm)	2,209
Front wheel track (mm)	1,702
Rear wheel track (mm)	1,704
Wheelbase (mm)	2,997

HEADROOM	
Maximum front row headroom (mm)	998
Maximum second row headroom (mm)	982

LEGROOM	
Maximum first row legroom (mm)	1,024
Maximum second row legroom (mm)	961

LOADSPACE CAPACITY **	
Height (mm)	793
Width (mm)	1,400
Width between arches (mm)	1,103
Length behind first row (mm)	1,827
Maximum loadspace volume behind first row - Dry* (litres)	1,491
Maximum loadspace volume behind first row - Wet** (litres)	1,860
Length behind second row (mm)	970
Maximum loadspace volume behind second row - Dry* (litres)	647
Maximum loadspace volume behind second row - Wet** (litres)	835

GROUND CLEARANCE - STANDARD	
Ride height (mm)	216 / 209†
Approach angle	– 26.1° / 22.5°††
Departure angle	– 25°
Ramp angle	– 21.5° / 26.7°†

GROUND CLEARANCE - OFF ROAD	
Ride height (mm)	280 / 273†
Approach angle	– 33.0° / 29.7°††
Departure angle	– 29.8°
Ramp angle	– 26.9° / 24.4°†

WADING DEPTH	
Maximum wading depth (mm)	900

TURNING CIRCLE	
Kerb-to-kerb Two wheel steering (m)	12.53
Kerb-to-kerb Four wheel steering (m)	10.95
Wall-to-wall Two wheel steering (m)	12.53
Wall-to-wall Four wheel steering (m)	10.59
Turns lock-to-lock (no. of turns)	2.8

CONTACT YOUR RETAILER

The figures provided are as a result of official manufacturer’s tests in accordance with EU legislation. For comparison purposes only. Real world figures may differ. CO<sub>2</sub>, Equivalent All-Electric Range (EAER) and fuel economy figures shown on this website are estimated and may vary according to wheel fitment and optional extras fitted. Definitive CO<sub>2</sub>, Equivalent All-Electric Range (EAER) and fuel economy figures will be confirmed by your retailer prior to order confirmation, together with final On the Road pricing. WLTP is the new official EU test used to calculate standardised fuel consumption and CO<sub>2</sub> figures for passenger cars.

\*Weights reflect vehicles to standard specifications. Optional extras increase weight. \*\*Includes a 75kg driver, full fluids and 90% fuel. †Includes full fluids and 90% fuel. ††Roof carrying is only available with fixed and sliding panoramic roofs.