

RANGE ROVER SPORT P550E BASE PLUS

SPECIFICATIONS

Feature and equipment changes from Autobiography variant

P550E BASE PLUS

Ebony headlining in lieu of Ebony Suedecloth headlining
No Configurable Cabin Lighting
No heated steering wheel
No heated windscreen
20-way non-massage seats
No heated washer jets
No full extended leather upgrade
Pixel headlights in lieu of Digital LED headlights
Standard metal roof in lieu of panoramic roof

From £ 113,995

Vehicle prices shown including VAT, delivery charges, and estimated government fees and duties.

17

CO₂ Emissions (from) (g/km)

376.7

Fuel consumption (up to) (mpg)

The figures provided are as a result of official manufacturer’s tests in accordance with EU legislation. For comparison purposes only. Real world figures may differ. CO₂, Equivalent All-Electric Range (EAER) and fuel economy figures shown on this website are estimated and may vary according to wheel fitment and optional extras fitted. Definitive CO₂, Equivalent All-Electric Range (EAER) and fuel economy figures will be confirmed by your retailer prior to order confirmation, together with final On the Road pricing. WLTP is the new official EU test used to calculate standardised fuel consumption and CO₂ figures for passenger cars.

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90% fuel. †Includes full fluids and 90% fuel. ††Roof carrying is only available with fixed and sliding panoramic roofs.

PERFORMANCE

Maximum speed mph (km/h)	150 (242)
Acceleration (secs) 0-60 mph (0-100 km/h) with Dynamic Launch	4.7 (4.9)

POWERTRAIN

Capacity (cc)	2,996
Maximum power (PS/rpm)	550 / 5,500-6,500
Maximum torque (Nm/rpm)	800 / 2,000 -5,000
Transmission	Automatic
Fuel tank capacity – useable litres	71.5

WEIGHTS (KG)*

Unladen weight (EU) (kg)	2,810
Unladen weight (DIN) (kg)	2,735
Gross Vehicle Weight (GVW) (kg)	3,450

TOWING (KG)

Unbraked trailer (kg)	750
Maximum towing (kg)	3,000
Maximum coupling point (nose weight) (kg)	120
Maximum vehicle and trailer combination	6,450

ROOF CARRYING (KG)††

Maximum roof load (including cross bars) (kg)	100
---	-----

DIMENSIONS

Maximum height (mm)	1,820
Overall length (mm)	4,946
Width with mirrors folded (mm)	2,047
Width with mirrors out (mm)	2,209
Front wheel track (mm)	1,702
Rear wheel track (mm)	1,704
Wheelbase (mm)	2,997

HEADROOM

Maximum front row headroom (mm)	998
Maximum second row headroom (mm)	982

LEGROOM

Maximum first row legroom (mm)	1,024
Maximum second row legroom (mm)	961

LOADSPACE CAPACITY **

Height (mm)	793
Width (mm)	1,400
Width between arches (mm)	1,103
Length behind first row (mm)	1,827
Maximum loadspace volume behind first row - Dry* (litres)	1,491
Maximum loadspace volume behind first row - Wet** (litres)	1,860
Length behind second row (mm)	970
Maximum loadspace volume behind second row - Dry* (litres)	647
Maximum loadspace volume behind second row - Wet** (litres)	835

GROUND CLEARANCE - STANDARD

Ride height (mm)	216 / 209†
Approach angle	– 26.1° / 22.5°††
Departure angle	– 25°
Ramp angle	– 21.5° / 26.7°†

GROUND CLEARANCE - OFF ROAD

Ride height (mm)	280 / 273†
Approach angle	– 33.0° / 29.7°††
Departure angle	– 29.8°
Ramp angle	– 26.9° / 24.4°†

WADING DEPTH

Maximum wading depth (mm)	900
---------------------------	-----

TURNING CIRCLE

Kerb-to-kerb Two wheel steering (m)	12.53
Kerb-to-kerb Four wheel steering (m)	10.95
Wall-to-wall Two wheel steering (m)	12.53
Wall-to-wall Four wheel steering (m)	10.59
Turns lock-to-lock (no. of turns)	2.8

CONTACT YOUR RETAILER