

DEFENDER OCTA BASE

SPECIFICATIONS

Feature and equipment changes from standard OCTA variant

OCTA BASE

Standard roof in lieu of panoramic roof
Manual close tailgate
No full size spare wheel
Sound system
No Head Up Display
No wireless device charging
No domestic plug socket
No loadspace cover
No signature carpet mats
No seat heating for 40:20:40 rear seats
Performance Seats without Body and Soul Seat function
Manual adjustable steering column
Ebony Morzine headlining

From **£148,045**

Vehicle prices shown including VAT, delivery charges, and estimated government fees and duties.

249

CO₂ Emissions (from) (g/km)

21.7

Fuel consumption (up to) (mpg)

PERFORMANCE

Maximum speed mph (km/h)	155 (250)
Acceleration secs 0-60mph (0-100 km/h)	3.8 (4.0)

POWERTRAIN

Capacity (cc)	4,395
Maximum power (HP/rpm)	635 / 5,855 - 7,000
Maximum torque (Nm/rpm)	750 / 1,800 - 5,855
Transmission	Automatic
Tank capacity (litres approx.)	90

WEIGHTS

Unladen weight (EU) (kg)	2,585 (5 Seat)
Unladen weight (DIN) (kg)	2,510 (5 Seat)
Gross Vehicle Weight (GVW) (kg)	3,230 (5 Seat)

TOWING

Unbraked trailer (kg)	750
Maximum towing (kg)	3,500
Maximum coupling point (nose weight) (kg)	150
Maximum vehicle and trailer combination (GTW) (kg)	6,730

ROOF CARRYING

Maximum roof load (including cross bars) (kg)	100
---	-----

DIMENSIONS

Height (mm)	1,995 (Air Suspension)
Length (mm)	4,813 (Without spare wheel)
Width with mirrors folded (mm)	2,064
Width with mirrors out (mm)	2,105
Front wheel track (mm)	1,772 (Air Suspension)
Rear wheel track (mm)	1,768 (Air Suspension)
Wheelbase (mm)	3,023

HEADROOM

Maximum first row / second row / third row headroom with standard roof (mm)	1,032 / 1,025 / NA
Maximum first row / second row / third row headroom with panoramic/fabric roof (mm)	1,032 / 1,025 / NA

LEGROOM

Maximum first row / second row / third row legroom (mm)	993 / 975 / NA
---	----------------

LOADSPACE CAPACITY

Height (mm)	904
Width (mm)	1,211
Width between arches (mm)	1,160
Length behind first row (mm)	1,763
Maximum loadspace volume behind first row - Dry (litres)	1,875
Maximum loadspace volume behind first row - Wet (litres)	2,277
Length behind second row (mm)	919
Maximum loadspace volume behind second row - Dry (litres)	786
Maximum loadspace volume behind second row - Wet (litres)	972
Length behind third row (mm)	–
Maximum loadspace volume behind third row - Dry (litres)	–
Maximum loadspace volume behind third row - Wet (litres)	–

GROUND CLEARANCE – STANDARD

Ride height (mm)	250 (246 at Rear Axle) (Air Suspension)
Approach angle	33.0° (Air Suspension)
Departure angle	38.2° (Air Suspension)
Ramp angle	22.9° (Air Suspension)

GROUND CLEARANCE – OFF ROAD

Ride height (mm)	323 (Air Suspension)
Approach angle	40.2° (Air Suspension)
Departure angle	42.8° (Air Suspension)
Ramp angle	29.0° (Air Suspension)

WADING DEPTH

Maximum wading depth (mm)	1,000 (Air Suspension)
---------------------------	------------------------

TURNING CIRCLE

Kerb-to-kerb (m)	12.84
Wall-to-wall (m)	13.14
Turns lock-to-lock (no. of turns)	2.39

The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real world figures may differ. CO₂, Equivalent All-Electric Range (EAER) and fuel economy figures shown on this website are estimated and may vary according to wheel fitment and optional extras fitted. Definitive CO₂, Equivalent All-Electric Range (EAER) and fuel economy figures will be confirmed by your retailer prior to order confirmation, together with final On the Road pricing. WLTP is the new official EU test used to calculate standardised fuel consumption and CO₂ figures for passenger cars.

CONTACT YOUR RETAILER