

RANGE ROVER SPORT EV550

SPECIFICATIONS

Feature and equipment changes from Autobiography variant

EV550 STANDARD

20" alloys in lieu of 21" alloys
LED Headlights with signature DRL in lieu of Pixel LED headlights with signature DRL
20 way seats in lieu of 8 way seats
Non heated steering wheel
Two Zone climate control in lieu of Four Zone
Sound System in lieu of Meridian Sound System

From £109,810

Vehicle prices shown including VAT, delivery charges, and estimated government fees and duties.

0

CO₂ Emissions (from) (g/km)

374

eAER (up to)(miles)

PERFORMANCE

Maximum speed mph (km/h)	124 (200)
Acceleration (secs) 0-60 mph (0-100 km/h)	4.3 (4.5)

POWERTRAIN

Capacity (cc)	N/A
Maximum power (PS/rpm)	550
Maximum torque (Nm)	850
Transmission	Single Speed
Useable Energy (kWh)	118.5

WEIGHTS (KG)*

Unladen weight (EU)**	2,770
Unladen weight (DIN)†	2,695
Gross Vehicle Weight (GVW)	3,580

TOWING (KG)

Unbraked trailer	750
Maximum towing	2500
Maximum coupling point (nose weight)	250
Maximum vehicle and trailer combination	5980

ROOF CARRYING (KG) **

Maximum roof load (including cross bars)	100
--	-----

DIMENSIONS

Maximum height (mm)	1,820
Overall length (mm)	4,946
Width with mirrors folded (mm)	2,047
Width with mirrors out (mm)	2,209
Front wheel track (mm)	1,702
Rear wheel track (mm)	1,704
Wheelbase (mm)	2,997

HEADROOM

Maximum front row headroom (mm)	998
Maximum second row headroom (mm)	982

LEGROOM (MM)

Maximum first row legroom	1,024
Maximum second row legroom	961

LOADSPACE CAPACITY

Height	793
Width (mm)	1,400
Width between arches (mm)	1,103
Length behind first row (mm)	1,827
Maximum loadspace volume behind first row - Dry (litres)	1,491
Maximum loadspace volume behind first row - Wet (litres)	1,860
Length behind second row (mm)	970
Maximum loadspace volume behind second row - Dry (litres)	647
Maximum loadspace volume behind second row - Wet (litres)	835

GROUND CLEARANCE - STANDARD

Ride height	216 / 209
Approach angle	-26.1° / 22.5°
Departure angle	25
Ramp angle	-21.5° / 26.7°

GROUND CLEARANCE - OFF ROAD

Ride height	280 / 273
Approach angle	-33.0° / 29.7°
Departure angle	29.8°
Ramp angle	-26.9° / 24.4°

WADING DEPTH

Maximum wading depth (mm)	900
---------------------------	-----

TURNING CIRCLE

Kerb-to-kerb Two wheel steering (m)	12.53
Kerb-to-kerb Four wheel steering (m)	10.95
Wall-to-wall Two wheel steering (m)	12.53
Wall-to-wall Four wheel steering (m)	10.59
Turns lock-to-lock (no. of turns)	2.8

The figures provided are as a result of official manufacturer’s tests in accordance with EU legislation. For comparison purposes only. Real world figures may differ. CO₂, Equivalent All-Electric Range (EAER) and fuel economy figures shown on this website are estimated and may vary according to wheel fitment and optional extras fitted. Definitive CO₂, Equivalent All-Electric Range (EAER) and fuel economy figures will be confirmed by your retailer prior to order confirmation, together with final On the Road pricing. WLTP is the new official EU test used to calculate standardised fuel consumption and CO₂ figures for passenger cars.

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90% fuel. † Includes full fluids and 90% fuel. ††Roof carrying is only available with fixed and sliding panoramic roofs.

CONTACT YOUR RETAILER