

TECHNICAL SPECIFICATION 2026

RANGE ROVER
EVOQUE



ENGINES AND TECHNICAL SPECIFICATION

The Range Rover Evoque features advanced engine options, providing new levels of performance, efficiency, and refinement.

There is a plug-in electric hybrid (PHEV) for all-electric, zero tailpipe emissions driving, as well as petrol and diesel engine options.

1

ENGINES

View available engines, their fuel economy and specifications.

2

DIMENSIONS AND CAPABILITIES

View the ride height, turning circle and other capability specifications.

ENGINES

ENGINE	PLUG-IN PETROL ELECTRIC HYBRID (PHEV)	
	P270e	
Transmission	Automatic	
Driveline	All Wheel Drive (AWD)	
Maximum power (PS / rpm)	269 / 5,000-5,500*	
Maximum torque (Nm / rpm)	540 / 2,000-3,250*	
Capacity (cc)	1,498	
No. of cylinders / Valves per cylinder	3 / 4	
Cylinder layout	Transverse	
Bore / stroke (mm)	83 / 92.3	
Compression ratio (:1)	10.5 +/- 0.5	
FUEL ECONOMY – WLTP**		
WLTP Consumption	Combined	mpg (l/100 km)
WLTP CO ₂ Emissions	Combined	(g/km)
Fuel tank capacity – useable litres		56.5
Selective Catalytic Reduction Filter / Gasoline Particulate Filter (SCRF / GPF)		■

■ Standard.

*When combined with electric motor. **The figures provided are as a result of official manufacturer's tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route.

ENGINES

PLUG-IN PETROL ELECTRIC HYBRID (PHEV)		
P270e		
BATTERY AND CHARGING TIMES		
Home Charger / Wall box 7kW		2 hours 12 minutes to 100%
Rapid DC Charger 32kW		30 mins to 80%
Domestic Plug 2.3kW		6 hours 42 minutes to 100%
Battery capacity Total (Usable) kWh		11.98
Charging cable length (m)		5
PERFORMANCE		
Acceleration (secs) 0-60 mph (0-100 km/h)		6.8 (7.2)
Maximum speed mph (km/h)		118 (190)
ELECTRIC MOTOR DATA		
Maximum power PS (kW)		109 (80)
Maximum torque (Nm)		260
EV Range TEL Combined (WLTP)* miles (km)		37 (60)
EV Range expected Real World data miles (km)		29 (47)
Brakes		
Front type		Twin piston, sliding caliper, Vented discs
Front diameter (mm)		349
Rear type		Single piston, sliding caliper, Vented discs
Rear diameter (mm)		325
Park brake diameter (mm)		325
WEIGHTS (kg)**		
Unladen weight (EU) [†]		2,157
Unladen weight (DIN) ^{††}		2,082
Gross Vehicle Weight (GVW)		2,660
TOWING (kg)		
Unbraked trailer		750
Maximum towing		Up to 1,600
Maximum coupling point (nose weight)		100
Maximum vehicle and trailer combination		4,260
ROOF CARRYING (kg)		
Maximum roof load (including cross bars)		75

*The figures provided are as a result of official manufacturer's tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route. **Weights reflect vehicles to standard specifications. Optional extras increase weight. [†]Includes a 75kg driver, full fluids and 90% fuel. ^{††}Includes full fluids and 90% fuel.

ENGINES

ENGINE	PETROL MILD HYBRID (MHEV)	
	P160	■
Mild Hybrid Electric Vehicle (MHEV)		
Transmission	Automatic	
Driveline	Front Wheel Drive (FWD)	
Maximum power (HP / rpm)	160 / 5,000	
Maximum torque (Nm / rpm)	260 / 1,600-4,000	
Capacity (cc)	1,498	
No. of cylinders / Valves per cylinder	3 / 4	
Cylinder layout	Transverse	
Bore / stroke (mm)	83 / 92.3	
Compression ratio (:1)	10.5 +/- 0.5	
FUEL ECONOMY – WLTP**		
WLTP Consumption	Low	mpg (l/100km)
	Medium	mpg (l/100km)
	High	mpg (l/100km)
	Extra High	mpg (l/100km)
	Combined	mpg (l/100km)
WLTP CO ₂ Emissions	Low	(g/km)
	Medium	(g/km)
	High	(g/km)
	Extra High	(g/km)
	Combined	(g/km)

■ Standard. – Not Available.

*The figures provided are NEDC calculated from official manufacturer's tests. Figures may vary according to environment and driving style. For comparison purposes only. Real-world figures may differ. **The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO₂ and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted. [†]When Efficiency Pack fitted.

ENGINES

FUEL ECONOMY – CONTINUED

Fuel tank capacity - useable litres	Large tank
Selective Catalytic Reduction Filter / Gasoline Particulate Filter (SCRF / GPF)	■

PERFORMANCE

Acceleration (secs) 0 - 60 mph (0 - 100 km/h)	9.7 (10.3)
Maximum speed mph (km/h)	124 (199)

BRAKES

Front type	Single piston sliding caliper, Vented discs (17" wheels) Twin piston sliding caliper, Vented discs (18"-20" wheels)
Front diameter (mm)	325 (17" wheels) 349 (18"-20" wheels)
Rear type	Single piston sliding caliper, Solid discs
Rear diameter (mm)	300
Park brake diameter (mm)	300

WEIGHTS (kg)*

Unladen weight (EU)**	1,792
Unladen weight (DIN)†	1,717
Gross Vehicle Weight (GVW)	2,300

TOWING (kg)

Unbraked trailer	-
Maximum towing	-
Maximum coupling point (nose weight)	-
Maximum vehicle and trailer combination	-

ROOF CARRYING (kg)

Maximum roof load (including cross bars)	75
--	----

PETROL MILD HYBRID (MHEV)

P160

Fuel tank capacity - useable litres	67
Selective Catalytic Reduction Filter / Gasoline Particulate Filter (SCRF / GPF)	■

PERFORMANCE

Acceleration (secs) 0 - 60 mph (0 - 100 km/h)	9.7 (10.3)
Maximum speed mph (km/h)	124 (199)

BRAKES

Front type	Single piston sliding caliper, Vented discs (17" wheels) Twin piston sliding caliper, Vented discs (18"-20" wheels)
Front diameter (mm)	325 (17" wheels) 349 (18"-20" wheels)
Rear type	Single piston sliding caliper, Solid discs
Rear diameter (mm)	300
Park brake diameter (mm)	300

WEIGHTS (kg)*

Unladen weight (EU)**	1,792
Unladen weight (DIN)†	1,717
Gross Vehicle Weight (GVW)	2,300

TOWING (kg)

Unbraked trailer	-
Maximum towing	-
Maximum coupling point (nose weight)	-
Maximum vehicle and trailer combination	-

ROOF CARRYING (kg)

Maximum roof load (including cross bars)	75
--	----

■ Standard - Not Available.

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90% fuel. †Includes full fluids and 90% fuel.

ENGINES

ENGINE	DIESEL MILD HYBRID (MHEV)		
	D165	D200	
Mild Hybrid Electric Vehicle (MHEV)	■	■	
Transmission	Automatic	Automatic	
Driveline	All Wheel Drive (AWD)	All Wheel Drive (AWD)	
Maximum power (PS / rpm)	163 / 3,500-4,250	204 / 3,750	
Maximum torque (Nm / rpm)	380 / 1,500-2,500	430 / 1,750-2,500	
Capacity (cc)	1.998	1.998	
No. of cylinders / Valves per cylinder	4 / 4	4 / 4	
Cylinder layout	Transverse	Transverse	
Bore / stroke (mm)	83 / 92.3	83 / 92.3	
Compression ratio (:1)	16.5 +/- 0.5	16.5 +/- 0.5	
FUEL ECONOMY – WLTP*			
WLTP Consumption	Low	mpg (l/100 km)	37.7-35.3 (7.5-8.0)†
	Medium	mpg (l/100 km)	44.6-40.7 (6.5-6.9)
	High	mpg (l/100 km)	51.1-48.9 (5.5-5.8)
	Extra High	mpg (l/100 km)	43.7-41.9 (6.5-6.7)
	Combined	mpg (l/100 km)	44.6-42.5 (6.3-6.7)
WLTP CO ₂ Emissions	Low	(g/km)	196-210†
	Medium	(g/km)	170-182
	High	(g/km)	145-151
	Extra High	(g/km)	169-177
	Combined	(g/km)	166-174

■ Standard.

*The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO₂ and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted. †When Efficiency Pack fitted.

ENGINES

DIESEL MILD HYBRID (MHEV)		
FUEL ECONOMY – CONTINUED	D165	D200
Fuel tank capacity - useable litres	54	54
	Large tank	65
Diesel Exhaust Fluid (DEF) - useable litres	12	12
	Large tank	17
Selective Catalytic Reduction Filter / Diesel Particulate Filter (SCRF / DPF)	■	■
PERFORMANCE		
Acceleration (secs) 0-60 mph (0-100 km/h)	9.2 (9.8)	7.9 (8.5)
Maximum speed mph (km/h)	120 (193)	120 (193)
BRAKES		
Front type	Single piston sliding caliper, Vented discs (17" wheels) Twin piston sliding caliper, Vented discs (18"-20" wheels)	Twin piston sliding caliper, Vented discs
Front diameter (mm)	325 (17" wheels) 349 (18"-20" wheels)	349
Rear type	Single piston sliding caliper, Solid discs	Single piston sliding caliper, Solid discs
Rear diameter (mm)	300	300
Park brake diameter (mm)	300	300
WEIGHTS (kg)*		
Unladen weight (EU)**	1,890	1,941
Unladen weight (DIN) [†]	1,815	1,866
Gross Vehicle Weight (GVW)	2,490	2,490
TOWING (kg)		
Unbraked trailer	750	750
Maximum towing	Up to 2,000	Up to 2,000
Maximum coupling point (nose weight)	100	100
Maximum vehicle and trailer combination	4,490	4,490
ROOF CARRYING (kg)		
Maximum roof load (including cross bars)	75	75

■ Standard.

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90% fuel. [†]Includes full fluids and 90% fuel.

DIMENSIONS AND CAPABILITIES

DIMENSIONS

Maximum height 1,649mm
Overall length 4,371mm
Width 1,996mm mirrors folded
Width 2,100mm mirrors out
Front wheel track 1,625.3mm
Rear wheel track 1,631.7mm
Wheelbase 2,681mm

TURNING CIRCLE

Kerb-to-kerb 11.6m
Wall-to-wall 11.9m
Turns lock-to-lock 2.3

WADING DEPTH

Maximum wading depth 530mm

HEADROOM

Maximum front / rear headroom with standard roof
989mm / 973mm
Maximum front / rear headroom with panoramic roof
950mm / 969mm (1,013mm* / 997mm*)

LEGROOM

Maximum front legroom 1,016mm
Maximum rear legroom 864mm

OBSTACLE CLEARANCE

Standard ride height 212mm / 211mm**

APPROACH AND DEPARTURE CLEARANCE[†]

Approach Angle - 25°[†]
Departure Angle - 30.6°[†]
Ramp Angle - 20.7° / 20.4° **

LOADSPACE CAPACITY

Height 702mm, Width 1,301mm
Loadspace width between arches 1,053mm
Length behind first row 1,576mm
Length behind second row 798mm
Maximum loadspace volume behind first row
Dry^{††} 1,156 litres, Wet[‡] 1,383 litres
Maximum loadspace volume behind second row
Dry^{††} 472 litres, Wet[‡] 591 litres



Maximum height
1,649mm

Width 1,996mm mirrors folded
Width 2,100mm mirrors out



Overall length 4,371mm



Rear wheel track 1,631.7mm

Weights and dimensions shown apply to standard-specification, unladen vehicles, which may be affected by optional features and equipment.

*When measured up to the panoramic roof glass. **P270e models only. [†]With tow eye cover removed. ^{††}Dry: Volume as measured with Verband Der Automobilindustrie-compliant solid blocks (200mm x 50mm x 100mm). Volume measured up to headliner. [‡]Wet: Volume as measured by simulating the loadspace filled with liquid. Volume measured up to headliner.

Vehicle shown is Autobiography in Tribeca Blue with optional features fitted (market dependent).