

ENGINES AND TECHNICAL SPECIFICATION

Range Rover features advanced engine options, providing new levels of performance, efficiency, and refinement. There is an extended range plug-in Electric Hybrid (PHEV) for all-electric, zero tailpipe emissions driving, as well as petrol and diesel engine options.

1

STANDARD WHEELBASE

View the available engines, their fuel economy and specifications.

2

LONG WHEELBASE / LONG WHEELBASE SEVEN SEATS

View the available engines, their fuel economy and specifications.

3

DIMENSIONS AND CAPABILITIES

View the ride height, turning circle and other capability specifications.

			PETROL ELECTRIC HYBRID (PHEV)		
POWERTRAIN	OWERTRAIN		P460e	P550e	
Plug-in Hybrid Electric Vehicle (PH	EV)	-	•	•	
Transmission			Automatic	Automatic	
Driveline			All Wheel Drive (AWD)	All Wheel Drive (AWD)	
Maximum power (HP / rpm)			460 / 5,500 - 6,500*	550 / 5,500 - 6,500*	
Maximum torque (Nm / rpm)			660 / 2,000 - 5,000	800 / 2,000 - 5,000	
Capacity (cc)			2,996	2,996	
No. of cylinders / Valves per cylind	er		6 / 4	6 / 4	
Cylinder layout			In-line	In-line In-line	
Bore / stroke (mm)			83 / 92.3	83 / 92.3	
Compression ratio (:1)			10.5	10.5	
FUEL ECONOMY – WLTP**					
EV Range (eAER)	Combined	miles (km)	74 - 68 (119 - 110)	72 - 68 (115 - 109)	
-	Low	mpg (I / 100km)	-	_	
	Medium	mpg (I / 100km)	-	_	
WLTP Consumption	High	mpg (l / 100km)	_	-	
	Extra High	mpg (I / 100km)	-	_	
	Combined	mpg (I / 100km)	397.9 - 357.6 (0.7 - 0.8)	392.3 - 353.1 (0.7 - 0.8)	
WLTP CO ₂ Emissions	Combined	g / km	15 - 19	16 - 19	
Fuel tank capacity - useable litres			71.5	71.5	
Salactiva Catalytic Paduction Filter	/ Gasoline Particulate Filter (SCF	PE / GPE)			

*When combined with electric motor. **The figures provided are as a result of official manufacturer's tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route.

[■] Standard - Not Available.

-	PETROL ELECTRIC HYBRID (PHEV)		
PERFORMANCE	P460e	P550e	
Acceleration (secs) 0-60 mph (0-100 km / h) with Dynamic Launch	5.5 (5.7)	4.8 (5.0)	
Maximum speed mph (km / h)	140 (225)	150 (242)	
BATTERY AND CHARGING TIMES			
Battery capacity total (Usable) kWh	38.2 (31.8)	38.2 (31.8)	
Home Charger / Wall box 7kW	5 hours to 100%	5 hours to 100%	
DC Charger 50kW	40 mins to 80%	40 mins to 80%	
Domestic Plug*	15 hours to 100%	15 hours to 100%	
Charging cable length (m)	5	5	
ELECTRIC MOTOR DATA			
Maximum Power HP (kW)	160 (117)	160 (117)	
Maximum Torque (Nm)	450	450	
EV Range Combined (WLTP**) miles (km)	74 - 68 (119 - 110)	72 - 68 (115 - 109)	
EV Range expected Real World data (up to)	57 (91)	56 (90)	
BRAKES			
Front type	Ventilated disc	Ventilated disc	
Front diameter (mm)	380	400	
Rear type	Ventilated disc	Ventilated disc	
Rear diameter (mm)	355	370	
Park Brake	Electric Park Brake (EPB) in	ntegrated into brake caliper	
WEIGHTS (kg) [†]			
Unladen weight (EU)††	2,770	2,810	
Unladen weight (DIN)‡	2,695	2,735	
Gross Vehicle Weight (GVW)	3,480	3,480	
TOWING (kg)			
Unbraked trailer	750	750	
Maximum towing	3,000	3,000	
Maximum coupling point (nose weight)	120	120	
Maximum vehicle and trailer combination	6,480	6,480	
ROOF CARRYING (kg)			
Maximum roof load (including cross bars)	100	100	

^{*}Optional Home charging cable required. **The figures provided are as a result of official manufacturer's tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route. †Weights reflect vehicles to standard specifications. Optional extras increase weight. †Includes a 75kg driver, full fluids and 90% fuel.

			PETROL V8 MILD HYBRID (MHEV)		
POWERTRAIN			P530	P615	
Transmission			Automatic	Automatic	
Driveline			All Wheel Drive (AWD)	All Wheel Drive (AWD)	
Maximum power (HP / rpm)			530 / 5,500 - 7,000	615 / 5,855 - 7,000	
Maximum torque (Nm / rpm)			750 / 1,800 - 4,500	750 / 1,800 - 5,400	
Capacity (cc)			4,395	4,395	
No. of cylinders / Valves per cylin	nder		8 / 4	8 / 4	
Cylinder layout			Longitudinal V	Longitudinal V	
Bore / stroke (mm)			89 / 88.3	89 / 88.3	
Compression ratio (:1)			10.5	10.5	
FUEL ECONOMY – WLTP*					
	Low	mpg (I / 100km)	14.6 - 14.4 (19.3 - 19.6)	14.5 - 14.4 (19.5 - 19.6)	
	Medium	mpg (l / 100km)	25.6 - 24.1 (11.0 - 11.7)	24.6 - 24.0 (11.5 - 11.8)	
WLTP Consumption	High	mpg (l / 100km)	30.7 - 29.1 (9.2 - 9.7)	29.5 - 28.8 (9.6 - 9.8)	
	Extra High	mpg (l / 100km)	27.7 - 26.0 (10.2 - 10.9)	26.2 - 25.5 (10.8 - 11.1)	
	Combined	mpg (l / 100km)	25.1 - 23.8 (11.3 - 11.9)	24.1 - 23.6 (11.7 - 12.0)	
	Low	g / km	438 - 444	442 - 445	
		g / km	250 - 265	260 - 267	
WLTP CO ₂ Emissions	High	g / km	209 - 220	217 - 222	
	Extra High	g / km	231 - 246	244 - 251	
	Combined	g / km	255 - 268	265 - 271	
Fuel tank capacity - useable litres	6		90	90	
Selective Catalytic Reduction Filter	er / Gasoline Particulate Filter (SCF	RF / GPF)			
			-		

Standard

^{*}The figures provided are as a result of official manufacturer's tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route.

	PETROL V8 MILD HYBRID (MHEV)		
PERFORMANCE	P530	P615	
Acceleration (secs) 0-60 mph (0-100 km / h) with Dynamic Launch	4.4 (4.6)	4.3 (4.5)	
Maximum speed mph (km / h)	155 (250)	162 (261)	
BRAKES			
Front type	Ventilated disc	Ventilated disc	
Front diameter (mm)	400	400	
Rear type	Ventilated disc	Ventilated disc	
Rear diameter (mm)	370	370	
Park Brake	Electric Park Brake (EPB) integrated	l into brake caliper	
WEIGHTS (kg)*			
Unladen weight (EU)**	2,585	2,791	
Unladen weight (DIN) [†]	2,510	2,716	
Gross Vehicle Weight (GVW)	3,380	3,380	
TOWING (kg)			
Unbraked trailer	750	750	
Maximum towing	3,500	3,500	
Maximum coupling point (nose weight)	150	150	
Maximum vehicle and trailer combination	6,880	6,880	
ROOF CARRYING (kg)			
Maximum roof load (including cross bars)	100	100	

⁻ Not Available.

^{*}Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90% fuel. †Includes full fluids and 90% fuel.

			DIESEL MILD HYBRID (MHEV)	
POWERTRAIN			D300	D350
Mild Hybrid Electric Vehicle (MH	IEV)			
Transmission			Automatic	Automatic
Driveline			All Wheel Drive (AWD)	All Wheel Drive (AWD)
Maximum power (HP / rpm)			300 / 4,000	350 / 4,000
Maximum torque (Nm / rpm)			650 / 1,500 - 2,500	700 / 1,500 - 3,000
Capacity (cc)			2,997	2,997
No. of cylinders / Valves per cylir	nder		6 / 4	6 / 4
Cylinder layout			In-line	In-line
Bore / stroke (mm)			83.0 / 92.3	83.0 / 92.3
Compression ratio (:1)			15.5	15.5
FUEL ECONOMY – WLTP*				
	Low	mpg (l / 100km)	24.6 - 23.2 (11.5 - 12.2)	24.6 - 23.1 (11.5 - 12.2)
	Medium	mpg (l / 100km)	40.0 - 37.8 (7.1 - 7.5)	40.1 -3 7.7 (7.0 - 7.5)
WLTP Consumption	High	mpg (l / 100km)	48.1 - 43.1 (5.9 - 6.5)	48.1 - 43.1 (5.9 - 6.6)
	Extra High	mpg (l / 100km)	40.5 - 35.0 (7.0 - 8.1)	40.5 - 35.0 (7.0 - 8.1)
	Combined	mpg (l / 100km)	38.9 - 35.2 (7.3 - 8.0)	39.0 - 35.2 (7.2 - 8.0)
	Low	g / km	301 - 320	301 - 320
	Medium	g / km	185 - 196	185 - 197
WLTP CO ₂ Emissions	High	g / km	154 - 172	154 - 172
	Extra High	g / km	183 - 211	183 - 212
	Combined	g / km	190 - 210	190 - 211
Fuel tank capacity - useable litre	es		80	80
Diesel Particulate Filter (DPF)				•

Standard

^{*}The figures provided are as a result of official manufacturer's tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route.

	DIESEL MILD HYBRID (MHEV)		
PERFORMANCE	D300	D350	
Acceleration (secs) 0-60mph (0-100km / h) with Dynamic Launch	6.3 (6.6)	5.7 (6.0)	
Maximum speed mph (km / h)	135 (218)	145 (234)	
BRAKES			
Front type	Ventilated disc	Ventilated disc	
Front diameter (mm)	380	380	
Rear type	Ventilated disc	Ventilated disc	
Rear diameter (mm)	355	355	
Park Brake	Electric Park Brake (EPB) inte	egrated into brake caliper	
WEIGHTS (kg)*			
Unladen weight (EU)**	2,505	2,505	
Unladen weight (DIN) [†]	2,430	2,430	
Gross Vehicle Weight (GVW)	3,350	3,350	
TOWING (kg)			
Unbraked trailer	750	750	
Maximum towing	3,500	3,500	
Maximum coupling point (nose weight)	150	150	
Maximum vehicle and trailer combination	6,850	6,850	
ROOF CARRYING (kg)			
Maximum roof load (including cross bars)	100	100	

		PETROL ELECTRIC HYBRID (PHEV)
		P460e
EV)		
		Automatic
		All Wheel Drive (AWD)
		460 / 5,500 - 6,500*
		660 / 2,000 - 5,000
		2,996
der		6 / 4
		In-line In-line
		83.0 / 92.3
		10.5
		5
Combined	miles (km)	71 - 68 (114 - 110)
Low	mpg (l / 100km)	-
Medium	mpg (l / 100km)	-
High	mpg (l / 100km)	-
Extra High	mpg (l / 100km)	-
Combined	mpg (l / 100km)	392.3 - 357.6 (0.7 - 0.8)
Combined	g / km	18 - 19
		71.5
er / Gasoline Particulate Filter (SCR	RF / GPF)	
	Combined Low Medium High Extra High Combined Combined	Combined miles (km)

[■] Standard - Not Available.

^{*}When combined with electric motor. **The figures provided are as a result of official manufacturer's tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route.

	PETROL ELECTRIC HYBRID (PHEV)
PERFORMANCE	P460e
Seating	5
Acceleration (secs) 0-60mph (0-100km / h) with Dynamic Launch	5.6 (5.8)
Maximum speed mph (km / h)	140 (225)
BATTERY AND CHARGING TIMES	
Battery capacity total (Usable) kWh	38.2 (31.8)
Home Charger / Wall box 7kW	5 hours to 100%
DC Charger 50kW	40 mins to 80%
Domestic Plug*	15 hours to 100%
Charging cable length (m)	5
ELECTRIC MOTOR DATA	
Maximum Power HP (kW)	160
Maximum Torque (Nm)	450
EV Range Combined (WLTP**) miles (km)	75 - 68 (121 - 110)
EV Range expected Real World data (up to) miles (km)	56 (90)
BRAKES	
Front type	Ventilated disc
Front diameter (mm)	380
Rear type	Ventilated disc
Rear diameter (mm)	355
Park Brake	Electric Park Brake (EPB) integrated into brake caliper
WEIGHTS (kg) [†]	
	5
Unladen weight (EU) ^{††}	2,810
Unladen weight (DIN)‡	2,735
Gross Vehicle Weight (GVW)	3,480
TOWING (kg)	
Seating	5
Unbraked trailer	_
Maximum towing	_
Maximum coupling point (nose weight)	_
Maximum vehicle and trailer combination	-
ROOF CARRYING (kg)	
Maximum roof load (including cross bars)	100

^{*}Optional Home charging cable required. **The figures provided are as a result of official manufacturer's tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route. †Weights reflect vehicles to standard specifications. Optional extras increase weight. †Includes a 75kg driver, full fluids and 90% fuel.

			PETROL V8		
POWERTRAIN			P530	P615	
Mild Hybrid Electric Vehicle (MHEV	′)				
Transmission			Automatic	Automatic	
Driveline			All Wheel Drive (AWD)	All Wheel Drive (AWD)	
Maximum power (HP / rpm)			530 / 5,000 - 7,000	615 / 5,855 - 7,000	
Maximum torque (Nm / rpm)			750 / 1,800 - 4,500	750 (1,800 - 5,400)	
Capacity (cc)			4,395	4,395	
No. of cylinders / Valves per cylind	er		8 / 4	8 / 4	
Cylinder layout			Longitudinal V	Longitudinal V	
Bore / stroke (mm)			89 / 88.3	89 / 88.3	
Compression ratio (:1)			10.5	10.5	
FUEL ECONOMY – WLTP*					
Seating			5 / 7	5	
EV Range (eAER)	Combined	miles (km)	-	-	
	Low	mpg (l / 100km)	14.6 - 14.4 (19.4 - 19.6) / 14.5 - 14.4 (19.5 - 19.6)	14.5 - 14.4 (19.5 - 19.6)	
	Medium	mpg (l / 100km)	25.1 - 23.9 (11.3 - 11.8) / 24.5 - 24.0 (11.5 - 11.7)	24.7 - 23.9 (11.5 - 11.8)	
WLTP Consumption	High	mpg (l / 100km)	30.2 - 28.8 (9.4 - 9.8) / 29.7 - 29.0 (9.5 - 9.7)	29.5- 28.6 (9.6 - 9.9)	
	Extra High	mpg (l / 100km)	27.3 - 25.7 (10.3 - 11.0) / 26.9 - 25.8 (10.5 - 10.9)	26.2 - 25.3 (10.8 - 11.2)	
	Combined	mpg (l / 100km)	24.7 - 23.6 (11.4 - 12.0) / 24.3 - 23.8 (11.6 - 11.9)	24.2 - 23.5 (11.7 - 12.0)	
	Low	g / km	440 - 445 / 442 - 444	442 - 445	
	Medium	g / km	255 - 268 / 261 - 266	260 - 268	
VLTP CO ₂ Emissions	High	g / km	212 - 222 / 215 - 221	217 - 223	
	Extra High	g / km	234 - 249 / 238 - 248	244 - 253	
	Combined	g / km	259 - 271 / 263 - 269	265 - 272	
Fuel tank capacity - useable litres			90	90	
Selective Catalytic Reduction Filter	/ Gasoline Particulate Filter (SCR	F / GPF)			

[■] Standar

^{*}The figures provided are as a result of official manufacturer's tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route.

	PETROL V8		
PERFORMANCE	P530	P615	
Seating	5/7	5	
Acceleration (secs) 0-60mph (0-100km / h) with Dynamic Launch	4.5 (4.7) / 4.6 (4.8)	4.4 (4.6)	
Maximum speed mph (km / h)	155 (250)	162 (261)	
BRAKES			
Front type	Ventilated disc	Ventilated disc	
Front diameter (mm)	400	400	
Rear type	Ventilated disc	Ventilated disc	
Rear diameter (mm)	370	370	
Park Brake	Electric Park Brake (EPB) int	egrated into brake caliper	
WEIGHTS (kg)*			
Seating	5/7	5	
Unladen weight (EU) **	2,708 / 2,810	2,785	
Unladen weight (DIN) [†]	2,663 / 2,735	2,710	
Gross Vehicle Weight (GVW)	3,400 / 3,480	3,400	
TOWING (kg)			
Seating	5/7	5	
Unbraked trailer	750	750	
Maximum towing	3,500	3,500	
Maximum coupling point (nose weight)	150	150	
Maximum vehicle and trailer combination	6,900 / 6,980	6,900	
ROOF CARRYING (kg)			
Maximum roof load (including cross bars)	100	100	

		·	DIESEL MILD HYBRID (MHEV)	
POWERTRAIN			D350	
Mild Hybrid Electric Vehicle (MHE	EV)			
Transmission			Automatic	
Driveline			All Wheel Drive (AWD)	
Maximum power (HP / rpm)			350 / 4,000	
Maximum torque (Nm / rpm)			700 / 1,500 - 3,000	
Capacity (cc)			2,997	
No. of cylinders / Valves per cylind	der		6 / 4	
Cylinder layout			In-line	
Bore / stroke (mm)			83 / 92.3	
Compression ratio (:1)			15.5	
FUEL ECONOMY – WLTP*				
Seating			5/7	
	Low	mpg (l / 100km)	24.4 - 23.0 (11.6 - 12.3) / 24.0 - 23.5 (11.8 - 12.0)	
	Medium	mpg (l / 100km)	39.7 - 37.6 (7.1 - 7.5) / 39.1 - 38.2 (7.2 - 7.4)	
WLTP Consumption	High	mpg (l / 100km)	47.6 - 43.1 (5.9 - 6.6) / 46.7 - 44.0 (6.1 - 6.4)	
	Extra High	mpg (l / 100km)	40.2 - 35.3 (7.0 - 8.0) / 39.5 - 35.9 (7.2 - 7.9)	
	Combined	mpg (l / 100km)	38.6 - 35.2 (7.3 - 8.0) / 37.9 - 35.8 (7.5 - 7.9)	
	Low	g/km	304 - 322 / 309 - 316	
	Medium	g / km	187 - 197 / 189 - 194	
WLTP CO ₂ Emissions	High	g/km	156 - 172 / 159 - 168	
	Extra High	g/km	185 - 210 / 188 - 207	
	Combined	g / km	192 - 211 / 196 - 207	
Fuel tank capacity - useable litres			80	
Selective Catalytic Reduction Filte	er / Gasoline Particulate Filter (SCF	F / GPF)		

■ Standar

^{*}The figures provided are as a result of official manufacturer's tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route.

	DIESEL MILD HYBRID (MHEV)	_
PERFORMANCE	D350	
Seating	5/7	
Acceleration (secs) 0-60mph (0-100km / h) with Dynamic Launch	5.8 (6.1) / 6.0 (6.3)	
Maximum speed mph (km / h)	145 (234)	
BRAKES		
Front type	Ventilated disc	
Front diameter (mm)	380	
Rear type	Ventilated disc	
Rear diameter (mm)	355	
Park Brake	Electric Park Brake (EPB) integrated into brake caliper	
WEIGHTS (kg)*		
Seating	5/7	
Unladen weight (EU)**	2,569 / 2,666	
Unladen weight (DIN)†	2,494 / 2,541	
Gross Vehicle Weight (GVW)	3,390 / 3,400	
TOWING (kg)		
Seating	5/7	
Unbraked trailer	750	
Maximum towing	3,500	
Maximum coupling point (nose weight)	150	
Maximum vehicle and trailer combination	6,890 / 6,900	
ROOF CARRYING (kg)		
Maximum roof load (including cross bars)	100	

DIMENSIONS AND CAPABILITIES

VEHICLE HEIGHT

Maximum height 1,867mm

OBSTACLE CLEARANCE

Off-road height (SWB / LWB) 291 mm / 290 mm Standard ride height (SWB / LWB) 216 mm / 215 mm

TURNING CIRCLE

Kerb-to-kerb (SWB / LWB) 10.95 m / 11.54 m Wall-to-wall (SWB / LWB) 11.37 m / 11.96 m Turns lock-to-lock 2.78

Width 2,047 mm mirrors folded Width 2,209 mm mirrors out



SWB / LWB / LWB 7 Seats



WADING DEPTH

Maximum wading depth 900 mm*

HEADROOM

Maximum front row headroom 999 mm Maximum second row headroom (SWB / LWB / LWB 7 Seats) 996.5 mm / 978.3 mm / 1,005 mm Maximum third row headroom (LWB 7 Seats) 909 mm

LEGROOM

Maximum front row legroom (SWB / LWB / LWB 7 Seats) 1,013 mm / 1,014 mm / 1,014 mm Maximum second row legroom (SWB / LWB[‡] / LWB 7 Seats) 1,027 mm / 1,220 mm / 1,027 mm Maximum third row legroom (LWB 7 Seats) 864 mm

LOADSPACE CAPACITY**

Height 845.8 mm Width (SWB / LWB / LWB 7 Seats) 1,444 mm / 1,444 mm / 1,255 mm Width between arches (SWB / LWB / LWB 7 Seats) 1,057.3 mm / 1,057.3 mm / 1,059 mm

Length behind first row (SWB / LWB / LWB 7 Seats) 1,975.5 mm / 2.165 mm / 2.175 mm

Maximum loadspace volume behind first row** (SWB / LWB / LWB 7 Seats) Dry[†] 1,841 / 2,176 / 2,050 litres Wet^{††} 2,335 / 2,727.6 / 2,601 litres

Length behind second row** (SWB / LWB / LWB 7 Seats) 1,092.6 mm / 1,093 mm / 1,286 mm

Maximum loadspace volume behind second row** (SWB / LWB / LWB 7 Seats) Dry[†] 818 / 818 / 857 litres Wet^{††} 1,050 / 1,050 / 1,061 litres

Length behind third row (LWB 7 Seats) 434 mm

Maximum loadspace volume behind third row (LWB 7 Seats) Dry[†] 212 litres Wet^{††} 312 litres



Wheelbase (SWB / LWB / LWB 7 Seats) 2,997 mm / 3,197 mm / 3,197 mm

Standard overall length (SWB / LWB / LWB 7 Seats) 5,052 mm / 5,252 mm / 5,252 mm



A B C	
Ride Height Departure Angle Ramp Angle (SWB / LWB 7 Seats) Approach Approach	Angle
Off-road 29.0° 27.5° / 25.7° / 25.7° 34.7°	
Standard 24.5° 21.5° / 20.1° / 20.1° 26.1°	

Weights and dimensions shown apply to standard-specification, unladen vehicles, which may be affected by optional features and equipment.

*Wading depth (25 deg entry and exit) 750 mm, Deep Fording depth (9 deg entry and exit) 900 mm. **Rear loadspace is reduced when Rear Executive Class seating is selected. Please contact your local retailer for more detail. †Dry: Volume as measured with VDA-compliant solid blocks (200 mm x 50 mm x 100 mm). ^{††}Wet: Volume as measured by simulating the loadspace filled with liquid. [‡]Effective Legroom is reduced on SV when Sensory Floor is fitted. Please note: Figures relate to Standard Wheelbase (SWB), Long Wheelbase (LWB), and Long Wheelbase Seven Seats (LWB 7 Seats) models unless stated. Figures shown may also differ for PHEV or SV models.



